

# Ropes > Specs

## ROPE SPECIFICATIONS

Find the right rope that meets all of your work and rescue specifications.

### CLASSIC STATIC

Diameter	Sheath/Core	Weight	MBS	Certifications
9 mm	Nylon/Nylon	53 g/m	21 kN (4720 lbf)	NFPA 1983 . CI 1801 . CE
10 mm	Nylon/Nylon	66 g/m	27 kN (6070 lbf)	NFPA 1983 . CI 1801 . CE
11 mm	Nylon/Nylon	80 g/m	30 kN (6700 lbf)	NFPA 1983 . CI. 1801 . CE
12.5 mm	Nylon/Nylon	104 g/m	43 kN (9700 lbf)	NFPA 1983 . CI 1801 . CE
16 mm	Nylon/Nylon	145 g/m	66.7 kN (15000 lbf)	NFPA 1983 . CI 1801

Max Wear Nylon/Nylon Please refer to Classic Static diameters above

### POLYESTER

Diameter	Sheath/Core	Weight	MBS	Certifications
10 mm Talon	Nylon/Polyester	64.2 g/m	22 kN (4950 lbf)	NFPA 1983 L
11 mm Talon	Nylon/Polyester	96 g/m	31 kN (6970 lbf)	NFPA 1983 L
11 mm Isostatic	Polyester/Polyester	96 g/m	31 kN (6970 lbf)	NFPA 1983 L
13 mm Isostatic	Polyester/Polyester	125 g/m	42 kN (9440 lbf)	NFPA 1983 G
11 mm Access Pro	Polyester/Nylon		33 kN (7418 lbf)	NFPA 1983 L

### ESCAPE

Diameter	Sheath/Core	Weight	MBS	Certifications
7.5 mm PER Escape	Nylon/Nylon	39 g/m	17 kN (3800 lbf)	NFPA 1983 E
9 mm PER Escape	Nylon/Nylon	66 g/m	21 kN (4720 lbf)	NFPA 1983 E
7 mm PER Element	Technora/Technora	44.3 g/m	21 kN (4720 lbf)	NFPA 1983 E
Hot Search	Kevlar	22.4 g/m	2700+ lbf	N/A
Rapid Search	Nylon/Nylon+Kevlar	43 g/m		N/A

continued on next page

Pigeon Mountain Industries, Inc.  
PO Box 803  
LaFayette, GA 30728

T: 800.282.7673  
F: 706.764.1437  
E: [custserv@pmirope.com](mailto:custserv@pmirope.com)  
W: [www.pmirope.com](http://www.pmirope.com)

**WATER**

Diameter	Sheath/Core	Weight	MBS	Certifications
5.5 mm Navigator	Polypropylene/Dyneema	17.3 g/m	8.9 kN (2000 lbf)	N/A
7mm Navigator	Polypropylene/Dyneema	22.9 g/m	13 kN (3300 lbf)	CI 1801 . NFPA Throw Rope
7 mm Throw	Nylon/Polypropylene	34 g/m	8.45 kN (1900 lbf)	N/A
10 mm Throw	Nylon/Polypropylene	62 g/m	16 kN (3600 lbf)	N/A
8 mm Economy	Polypropylene	31 g/m	5.3 kN (1200 lbf)	N/A
10 mm Economy	Polypropylene	41 g/m	8 kN (1800 lbf)	N/A

**STATIC SPECIALTY**

Diameter	Sheath/Core	MBS	Certifications
9 mm PMI Sport	Nylon/Nylon	21 kN (4720 lbf)	CI 1801
10 mm PMI Sport	Nylon/Nylon	27 kN (6070 lbf)	CI 1801
11 mm PMI Sport	Nylon/Nylon	30 kN (6700 lbf)	CI 1801
12.5 mm PMI Sport	Nylon/Nylon	43 kN (9700 lbf)	CI 1801
10 mm Retro Reflective	Nylon/Nylon	27 kN (6070 lbf)	NFPA 1983
12.5 mm Retro Reflective	Nylon/Nylon	43 kN (9700 lbf)	NFPA 1983
9 mm Passage	Nylon/Nylon	21 kN (4720 lbf)	NFPA 1983 . CI 1801 CE
10 mm Passage	Nylon/Nylon	27 kN (6070 lbf)	NFPA 1983 . CI 1801 CE
11 mm Passage	Nylon/Nylon	30 kN (6700 lbf)	NFPA 1983 . CI 1801 CE
11 mm PIT Rope	Nylon/Nylon	30 kN (6700 lbf)	CI 1801

**DYNAMIC**

Diameter	Sheath/Core	Weight	Imact Force	Falls	Certifications
10.6 mm Wall Rope	Nylon/Nylon	69 g/m	8.2 kN	8	UIAA
10.2 mm Spire	Nylon/Nylon	69.4 g/m	7.9 kN	11	UIAA
10.6 mm Cirque	Nylon/Nylon	70 g/m	8 kN	12	UIAA
11 mm Latitude	Nylon/Nylon	81 g/m	8.5 kN	16	UIAA

Pigeon Mountain Industries, Inc.  
 PO Box 803  
 LaFayette, GA 30728

T: 800.282.7673  
 F: 706.764.1437  
 E: [custserv@pmirope.com](mailto:custserv@pmirope.com)  
 W: [www.pmirope.com](http://www.pmirope.com)