

A brand new PMI rope, HeatShield™ is an excellent choice for rope access work for anyone needing rope with superior sheath abrasion and heat resistant properties such as those performing work at bridges, dams, towers or industrial sites. If there is a chance your rope may contact a sharp edge, hot pipes, or anything hot nearby, consider this rope for the job. The sheath is 100% Technora® featuring a high tensile strength, good fatigue resistance, heat resistance, excellent dimensional stability, and chemical resistance.

Key Features:

Sheath - 100% Technora® • Core - 100% Nylon 6.6 • High modulus of elasticity • Low creep • Low thermal shrinkage

11 mm (7/16")

Weight: 84.1 g/m

MBS: 29.5 kN (6635 lbf)

Elongation: 2.4% at 300 lbf | 5.1% at 600 lbf | 8.2% at 1000 lbf

Elongation @ 10% MBS: 8.6%

Material: Technora® Sheath/Nylon Core

Color: Natural Gold

183 m (600 ft) HS110TG183A

> 183 meter order HS110TG001A

Custom orders accepted only for lengths longer than 183 m



12.5 mm (1/2")

Weight: 110.9 g/m

MBS: 44.2 kN kN (9944 lbf)

Elongation: 2.5% at 300 lbf | 5.0% at 600 lbf | 7.6% at 1000 lbf

Elongation @ 10% MBS: 8.8%


Material: Technora® Sheath/Nylon Core

Color: Natural Gold

183 m (600 ft) HS125TG183A

> 183 meter order HS125TG001A

Custom orders accepted only for lengths longer than 183 m



A large, empty rectangular box with a thin black border, intended for handwritten notes or a signature.

Pigeon Mountain Industries, Inc. | PO Box 803, LaFayette, GA 30278 | Fax: 706-764-1531 | Email: custserv@pmirope.com